



EuroXciser Derby 450 E

four horse, fifty foot diameter machine
 controller with simple user interface,
 providing speed ranges up to 20 mph,
 forward and reverse functions, and
 emergency stop

outside gate for easy horse loading and
 inside gate for inner ring access

X stand option, requiring no cement pad
 for base mount

metal partitions with fencer system

Derby 450 E EuroXciser machine

Capacity: 4 Horses Outer Diameter: 50' (15.24 m) Track Width: 8' (2.44 m) Speed: 0-20 mph (33 kph)

Features and Specifications

Horse Capacity: 4 Horse

Speed Range: 0-20 mph (0-33 kph)

Track Center Diameter: 42 feet (12.8 m)

Partition Separation - horse space (c/l): 33 feet (10 m)

Motor Drive: 0.75 hp

Controller: forward/reverse, on/off, dial speed command

Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer

Certification: CE, UL/CSA

Suspension: Pivoting Arms and Partitions

Finish: Galvanized Steel frame

Warranty: 10 years frame, motor/gear, turntable, 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

Optional Features: Program Controller, Motor Upgrade, Rubber Partitions, X stand to eliminate cement mount, fencing system

Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge

Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements

Track Covers: Track Cover available with this machine

Mounting: Cement pad anchor bolt or X stand

Grading: 0 percent grade, 5' greater than machine diameter