



## EuroXciser Derby 460 C

four horse, sixty foot diameter ceiling mounted machine

controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop

outside gate for easy horse loading and inside gate for inner ring access

full specifications provided for architect for structure requirements

metal partitions with fencer system

### Derby 460 C EuroXciser machine

Capacity: 4 Horses    Outer Diameter: 60' (18.3 m)    Track Width: 8' (2.44 m)    Speed: 0-25 mph (41 kph)

### Features and Specifications

**Horse Capacity:** 4 Horse

**Speed Range:** 0-25 mph (0-41 kph)

**Track Center Diameter:** 52 feet (15.8 m)

**Partition Separation - horse stall space (c/l):** 32.7 feet (10 m)

**Motor Drive:** 1.5 hp

**Controller:** forward/reverse, on/off, dial speed command

**Electrical:** 220V single phase 60 Hertz to motor, Std 115V fencer

**Certification:** CE, UL/CSA

**Suspension:** Pivoting Arms and Partitions

**Finish:** Galvanized Steel frame

**Warranty:** 10 years frame. motor/gear. turntable. 1 year electric

**Standard Features:** Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

**Optional Features:** Program Controller, Rubber Partitions, fencing system

**Other Customization Options:** Customize the diameter of the machine to fit space constraints at no additional charge

**Fencing:** Model I, Model II or Model III fencing, or customize your own - we will provide requirements

**Mounting:** Rafter mounted requirement, 2700 pound load

**Space requirements:** 5' above rafter line, 18' above ground.

**Inside Pen:** Inside diameter pen 44', with 11' clearance



## EuroXciser Derby 660 C

six horse, sixty foot diameter ceiling mounted machine

controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop

outside gate for easy horse loading and inside gate for inner ring access

full specifications provided for architect for structure requirements

metal partitions with fencer system

### Derby 660 C EuroXciser machine

Capacity: 6 Horses    Outer Diameter: 60' (18.3 m)    Track Width: 8' (2.44 m)    Speed: 0-25 mph (41 kph)

### Features and Specifications

**Horse Capacity:** 6 Horse

**Speed Range:** 0-25 mph (0-41 kph)

**Track Center Diameter:** 52 feet (15.8 m)

**Partition Separation - horse stall space (c/l):** 32.7 feet (10 m)

**Motor Drive:** 1.5 hp

**Controller:** forward/reverse, on/off, dial speed command

**Electrical:** 220V single phase 60 Hertz to motor, Std 115V fencer

**Certification:** CE, UL/CSA

**Suspension:** Pivoting Arms and Partitions

**Finish:** Galvanized Steel frame

**Warranty:** 10 years frame. motor/gear. turntable. 1 year electric

**Standard Features:** Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

**Optional Features:** Program Controller, Rubber Partitions, fencing system

**Other Customization Options:** Customize the diameter of the machine to fit space constraints at no additional charge

**Fencing:** Model I, Model II or Model III fencing, or customize your own - we will provide requirements

**Mounting:** Rafter mounted requirement, 2700 pound load

**Space requirements:** 5' above rafter line, 18' above ground.

**Inside Pen:** Inside diameter pen 44', with 11' clearance



## EuroXciser Derby 670 C



six horse, seventy foot diameter ceiling mounted machine

controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop

outside gate for easy horse loading and inside gate for inner ring access

full specifications provided for architect for structure requirements

metal partitions with fencer system

### Derby 670 C EuroXciser machine

Capacity: 6 Horses    Outer Diameter: 70' (21.3 m)    Track Width: 8' (2.44 m)    Speed: 0-25 mph (41 kph)

### Features and Specifications

**Horse Capacity:** 6 Horse

**Speed Range:** 0-25 mph (0-41 kph)

**Track Center Diameter:** 62 feet (18.9 m)

**Partition Separation - horse stall space (c/l):** 32.5 feet (9.9 m)

**Motor Drive:** 2.0 hp

**Controller:** forward/reverse, on/off, dial speed command

**Electrical:** 220V single phase 60 Hertz to motor, Std 115V fencer

**Certification:** CE, UL/CSA

**Suspension:** Pivoting Arms and Partitions

**Finish:** Galvanized Steel frame

**Warranty:** 10 years frame, motor/gear, turntable, 1 year electric

**Standard Features:** Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

**Optional Features:** Program Controller, Rubber Partitions, fencing system

**Other Customization Options:** Customize the diameter of the machine to fit space constraints at no additional charge

**Fencing:** Model I, Model II or Model III fencing, or customize your own - we will provide requirements

**Mounting:** Rafter mounted requirement, 2700 pound load

**Space requirements:** 5' min rafter to roof, 18' rafter to ground

**Inside Pen:** Inside diameter pen 54', with 11' clearance