



EuroXciser Derby 460

- four horse, sixty foot diameter machine
- controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop
- outside gate for easy horse loading and inside gate for inner ring access
- anchor mount to cement base
- metal partitions with fencer system

Derby 460 EuroXciser machine

Capacity: 4 Horses Outer Diameter: 60' (18.28 m) Track Width: 8' (2.44 m) Speed: 0-25 mph (41 kph)

Features and Specifications

Horse Capacity: 4 Horse
Speed Range: 0-25 mph (0-41 kph)
Track Center Diameter: 52 feet (15.84 m)
Partition Separation - horse stall space (c/l): 40.8 feet (12.4 m)
Motor Drive: 1.5 hp
Controller: forward/reverse, on/off, dial speed command
Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer
Certification: CE, UL/CSA
Suspension: Pivoting Arms and Partitions
Finish: Galvanized Steel frame
Warranty: 10 years frame. motor/gear. turntable. 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.
Optional Features: Program Controller, Motor Upgrade, Rubber Partitions, fencing system
Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge
Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements
Track Covers: Track Cover available with this machine
Mounting: Cement pad anchor bolt
Grading: 0 percent grade, 5' greater than machine diameter



EuroXciser Derby 560

five horse, sixty foot diameter machine
 controller with simple user interface,
 providing speed ranges up to 25 mph,
 forward and reverse functions, and
 emergency stop

outside gate for easy horse loading and
 inside gate for inner ring access

anchor mount to cement base

metal partitions with fencer system

Derby 560 EuroXciser machine

Capacity: 5 Horses Outer Diameter: 60' (18.28 m) Track Width: 8' (2.44 m) Speed: 0-20 mph (33 kph)

Features and Specifications

Horse Capacity: 5 Horse

Speed Range: 0-20 mph (0-33 kph)

Track Center Diameter: 52 feet (15.84 m)

Partition Separation - horse stall space (c/l): 32.7 feet (10 m)

Motor Drive: 1.5 hp

Controller: forward/reverse, on/off, dial speed command

Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer

Certification: CE, UL/CSA

Suspension: Pivoting Arms and Partitions

Finish: Galvanized Steel frame

Warranty: 10 years frame, motor/gear, turntable, 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

Optional Features: Program Controller, Motor Upgrade, Rubber Partitions, fencing system

Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge

Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements

Track Covers: Track Cover available with this machine

Mounting: Cement pad anchor bolt

Grading: 0 percent grade, 5' greater than machine diameter



EuroXciser Derby 660

six horse, sixty foot diameter machine

controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop

outside gate for easy horse loading and inside gate for inner ring access

anchor mount to cement base

metal partitions with fencer system

Derby 660 EuroXciser machine

Capacity: 6 Horses Outer Diameter: 60' (18.28 m) Track Width: 8' (2.44 m) Speed: 0-25 mph (41 kph)

Features and Specifications

Horse Capacity: 6 Horse

Speed Range: 0-25 mph (0-41 kph)

Track Center Diameter: 52 feet (15.84 m)

Partition Separation - horse stall space (c/l): 27.2 feet (8.3 m)

Motor Drive: 1.5 hp

Controller: forward/reverse, on/off, dial speed command

Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer

Certification: CE, UL/CSA

Suspension: Pivoting Arms and Partitions

Finish: Galvanized Steel frame

Warranty: 10 years frame. motor/gear. turntable. 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

Optional Features: Progam Controller, Motor Upgrade, Rubber Partitions, fencing system

Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge

Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements

Track Covers: Track Cover available with this machine

Mounting: Cement pad anchor bolt

Grading: 0 percent grade, 5' greater than machine diameter



EuroXciser Derby 565

- five horse, sixty five foot diameter machine
- controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop
- outside gate for easy horse loading and inside gate for inner ring access
- anchor mount to cement base
- metal partitions with fencer system

Derby 565 EuroXciser machine

Capacity: 5 Horses Outer Diameter: 65' (19.8 m) Track Width: 8' (2.44 m) Speed: 0-25 mph (41 kph)

Features and Specifications

Horse Capacity: 5 Horse
Speed Range: 0-25 mph (0-41 kph)
Track Center Diameter: 57 feet (17.4 m)
Partition Separation - horse stall space (c/l): 35.8 feet (10.9 m)
Motor Drive: 1.5 hp
Controller: forward/reverse, on/off, dial speed command
Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer
Certification: CE, UL/CSA
Suspension: Pivoting Arms and Partitions
Finish: Galvanized Steel frame
Warranty: 10 years frame. motor/gear. turntable. 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.
Optional Features: Program Controller, Motor Upgrade, Rubber Partitions, fencing system
Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge
Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements
Track Covers: Track Cover available with this machine
Mounting: Cement pad anchor bolt
Grading: 0 percent grade, 5' greater than machine diameter



EuroXciser Derby 665

- six horse, sixty five foot diameter machine
- controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop
- outside gate for easy horse loading and inside gate for inner ring access
- anchor mount to cement base
- metal partitions with fencer system

Derby 665 EuroXciser machine

Capacity: 6 Horses Outer Diameter: 65' (19.8 m) Track Width: 8' (2.44 m) Speed: 0-25 mph (41 kph)

Features and Specifications

Horse Capacity: 6 Horse
Speed Range: 0-25 mph (0-41 kph)
Track Center Diameter: 57 feet (17.4 m)
Partition Separation - horse stall space (c/l): 29.8 feet (9.1 m)
Motor Drive: 1.5 hp
Controller: forward/reverse, on/off, dial speed command
Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer
Certification: CE, UL/CSA
Suspension: Pivoting Arms and Partitions
Finish: Galvanized Steel frame
Warranty: 10 years frame. motor/gear. turntable. 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.
Optional Features: Program Controller, Motor Upgrade, Rubber Partitions, fencing system
Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge
Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements
Track Covers: Track Cover available with this machine
Mounting: Cement pad anchor bolt
Grading: 0 percent grade, 5' greater than machine diameter

EuroXciser Derby 672



six horse, seventy two foot diameter machine

controller with simple user interface, providing speed ranges up to 25 mph, forward and reverse functions, and emergency stop

outside gate for easy horse loading and inside gate for inner ring access

anchor mount to cement base

metal partitions with fencer

Derby 672 EuroXciser machine

Capacity: 6 Horses Outer Diameter: 72' (21.9 m) Track Width: 8' (2.44 m) Speed: 0-25 mph (41 kph)

Features and Specifications

Horse Capacity: 6 Horse

Speed Range: 0-25 mph (0-41 kph)

Track Center Diameter: 64 feet (19.5 m)

Partition Separation - horse stall space (c/l): 33.5 feet (10.2 m)

Motor Drive: 2.0 hp

Controller: forward/reverse, on/off, dial speed command

Electrical: 220V single phase 60 Hertz to motor, Std 115V fencer

Certification: CE, UL/CSA

Suspension: Pivoting Arms and Partitions

Finish: Galvanized Steel frame

Warranty: 10 years frame. motor/gear. turntable. 1 year electric

Standard Features: Galvanized Base with factory assembled drive train (motor/gear, coupler, flange, turn table, fencer). Galvanized arms and partitions. Stainless Steel pre-fab cables for simple installation.

Optional Features: Program Controller, Rubber Partitions, fencing system

Other Customization Options: Customize the diameter of the machine to fit space constraints at no additional charge

Fencing: Model I, Model II or Model III fencing, or customize your own - we will provide requirements

Track Covers: Track Cover available with this machine

Mounting: Cement pad anchor bolt

Grading: 0 percent grade, 5' greater than machine diameter